

SDI



GRIP SHEET®

Paper Weight	120 g/m ²
Paper Type	Recycled
Coating	100% 2 Sides
Sheet Size	1220 mm x 1016 mm (48" x 40")
	+/- 5mm (0.25")

TECHNICAL DATA*

Finish Product Weight	154 g/m ²	NF EN ISO 536, 1996
Thickness	304 µm	NF EN ISO 534, 2005
Burst Index	462 kPa	NF EN ISO 2758, 2004
Friction Coefficient		NF Q 03-083, 1993
	Machine Direction	27.9°
Air Porosity	17 cm ³ /m ² .Pas	
Toxicity	None	
Skin Irritation	None	
Reusable	Yes	
Recyclable	Yes	

Breaking Strength in Tension

Resistance		NF EN ISO 1924.2, 1995
	Machine Direction	7.83 kN/m
	Cross Direction	3.8 kN/m
Rupture Length		
	Machine Direction	5182 m
	Cross Direction	2517 m
Elongation		
	Machine Direction	1.9%
	Cross Direction	2.9%

PACKAGING DATA

Pallet Size	1200 mm X 1000 mm (47,25" x 39,25")
Quantity per Box	35
Quantity per Pallet	3 500
Unit Load Height	Up to 1194 mm (47") approximately
Unit Load Weight	682 kg (1500 lbs) approximately
Stocking Conditions	Non-sensitive to heat or cold Double stacking is acceptable for storage only

* **Important Note:** Considering the characteristics of coating, the specifications, especially the coefficient of friction can only be measured for the fully coated version (2 side coating). Other characteristics should be very similar but are provided for reference only. Specifications data supplied by Endupack SA.

Property of SDI Packaging Inc., 10310 Ray-Lawson Blvd., Anjou, QC, Canada H1J 1M1

