



SPECIFICATIONS

Clear Grip 105g/m² (75µm)

Date: 2015-03-16

GENERAL	
Base Material	PET
Non Slip Coating	100% Coated on 2 sides

	TESTS	NORM	UNIT	SM/ST	MAIN VALUE	DEVIATION
TEXTURE	Weight	NFT 54-101	g/m ²		135,1	1,4
	Thickness		µm		218,6	4,1
	Density (23°C)	ASTM D. 1505	g/cm ³		1,395	
MECHANICAL PROPERTIES	Breaking strength in traction	ASTM D.882	daN/mm ²		18	
	Elongation		%		140	
AIR/WATER POROSITY	COBB 60S	T441-0M98	g/m ²	recto	10	
			g/m ²	verso	10	
FRICTION	Static friction coefficient	ISO 8295		SM	0,99	0,09
	Sliding angle		°	SM	44,7	
HEALTH	Toxicity				none	
	Skin irritation				none	
	Food contact aptitude	REG. N CE 1935-2004			Exemption of food contact aptitude in normal condition of use	
ENVIRONMENT	Reuse	NF 13429			yes	
	Content of recycled	measured	%		0	

* Specifications data supplied by Endupack

* **MD**: Machine Direction ; **CD**: Cross Direction

STANDARD PACKAGING	
Sheet Size	1200 mm X 1000 mm +/- 5 mm (47.25" X 39.25" +/- 0.25") and other
Pallet Size	1200 mm X 1000 mm (approx. 47.25" X 39.25")
Quantity per pallet	2000 sheets and other
Stocking conditions	Non sensitive to heat or cold. Double stacking is acceptable for storage only.
Property of SDI Packaging Inc., 10310 Ray-Lawson Blvd., Anjou, QC, Canada H1J 1M1	

