



SPECIFICATIONS

G220K2M45X37

GRIP SHEET NON-SLIP SHEET

Date: 2009-12-03

GENERAL DESCRIPTION	
Base Material	Recycled paper of a basic weight of 220g per square meter
Non Slip Coating	Fully Coated on both sides (Alternating Bands and one-side also available)

TECHNICAL CHARACTERISTICS **See Important Note					
TEST	UNITS	STANDARD	NOTE	TARGET	SPECIFICATIONS
Finish Product Weight	g/m ²	NF EN ISO 536, 1996		241	232 - 249
Thickness	µm	NF EN ISO 534, 2005		418	398 - 438
Resistance to Break under Traction		NF EN ISO 1924.2, 1995			
Resistance	kN/m		MD	10.3	≥ 8.27
			CD	4.4	≥ 3.88
Length at Break	meter		MD	4346	≥ 3500
			CD	1869	≥ 1640
Elongation	%		MD	1.6	≥ 0.8
			CD	2.4	≥ 1.5
Bursting Strength	kPa	NF EN ISO 2758, 2004		388	≥ 297
Coefficient of Static Friction (recto against verso - Angle)	in degree	NF Q 03-083, 1993	MD	53.0	≥ 46.9

**** Important Note:** At the time this specification was produced, the technical characteristics were only available for the fully coated version. Data supplied by Endupack SA.

PACKAGING	
Standard Sheet Size	1140 mm X 940 mm +/- 5 mm (45" X 37" +/- 0.25")
Pallet Size	1200 mm X 1000 mm (+/- 48" X 40")
Quantity per pallet	2000 sheets
Unit Load Height	Up to 44" approximately
Unit Load Weight	1180 lbs (535 kg) approximately
Stocking conditions	Non sensitive to heat or cold. Double stacking is acceptable.

Property of SDI Packaging Inc., 10310 Ray-Lawson Blvd., Anjou, QC, Canada H1J 1M1