



# SPECIFICATIONS

G240P2A1200X1000

GRIP SHEET NON-SLIP SHEET

Date: 2010-02-02

GENERAL DESCRIPTION	
<b>Base Material</b>	PE coated paper - issued from photo paper process as non-conform
<b>Non Slip Coating</b>	Alternating Bands, Light Coating

TECHNICAL CHARACTERISTICS					
TEST	UNITS	STANDARD	NOTE	TARGET	SPECIFICATIONS
<b>Finish Product Weight</b>	g/m <sup>2</sup>	NF EN ISO 536, 1996		243	238 - 249
<b>Thickness</b>	µm	NF EN ISO 534, 2005		329	314 - 343
<b>Resistance to Break under Traction</b>		NF EN ISO 1924.2, 1995			
<b>Resistance</b>	kN/m		MD	10.9	≥ 10.2
			CD	7.1	≥ 6.46
<b>Length at Break</b>	meter		MD	4549	≥ 4275
			CD	2967	≥ 2710
<b>Elongation</b>	%		MD	2.6	≥ 2.2
			CD	6.5	≥ 5.5
<b>Bursting Strength</b>	kPa	NF EN ISO 2758, 2004		462	≥ 385
<b>Coefficient of Static Friction</b> (recto against verso - Angle)	in degree	NF Q 03-083, 1993	MD	27.9	≥ 22

STANDARD PACKAGING	
<b>Sheet Size</b>	1200 mm X 1000 mm +/- 5 mm (47.25" X 39.3" +/- 0.25")
<b>Pallet Size</b>	1200 mm X 1000 mm (approx. 47.25" X 39.3")
<b>Quantity per pallet</b>	2000 sheets
<b>Unit Load Height</b>	Up to 34" approximately
<b>Unit Load Weight</b>	1450 lbs (658 kg) approximately
<b>Stocking conditions</b>	Non sensitive to heat or cold. Double stacking is acceptable.
Property of SDI Packaging Inc., 10310 Ray-Lawson Blvd., Anjou, QC, Canada H1J 1M1	